

**Specifications for Industrial Tubes (Size 14.00 x 24)**  
**For Lift Trucks.**

No	Description	SLPA requirements	Supplier's Specifications
1.	<b>General Application</b>	To be heavy duty type for the use on 14.00x24 tyres fitted to Heavy Lift Trucks.	
2.	<b>Type of the valve</b>	<b>Bend Type, removable Valve</b>	
3.	<b>Length of the valve</b>	i) Shall be between 5" and 6"	
4.	<b>Make</b>	To be of reputed make. Make to be indicated.	
5.	<b>Country of Origin</b>	To be indicated	
6.	<b>Standards</b>	1. Shall have ISO 9000 series standard certification for manufacturing process.	
		2. Any other acceptable quality certificates to be indicated	
7.	<b>Life span</b>	Guaranteed life span should not be less than 6 months from the date of purchase. (To be indicated and proved with copies of certificates)	
8.	<b>The surface texture</b>	The tube surface shall be uniform and sufficiently smooth for the puncher repairs.	
9.	<b>Thickness of the tube</b>	Shall be uniform throughout the surface.	
10.	<b>Tube Pressure</b>	Shall be withstand to pressure of 115 PSI, when tube is inflated inside the tyre.	
11.	<b>Delivery Period</b>	To be mentioned/ (shall be not more than 30 days)	
12.	<b>Manufacturers Genuines Certificate</b>	To be supply with the goods.	
13.	<b>Sample for inspection</b>	1 No of Sample to be provided	
14.	<b>Unit Price (Rs.)</b>	To be mentioned	

**Note:** a) Copies of all certificate and catalogues should be provided in support of above Information.

b) The offers without proven details and sample will be rejected.

c) The samples will not be given back to the supplier.