

FILE NO - CMS/LP/17/SQ/03/098

SPECIFICATIONS FOR INDUSTRIAL TYRES 8.25x15-14PR

	Description	SLPA's Requirement	Supplier's Specifications
1	General	To be Heavy duty Industrial Tube Type and classified by manufacturer for the use of Fork Lift applications. (Please attach the copy of catalogue showing all technical details)	
2	Size	8.25x15-14PR	
3	Make	To be of proven make (Make to be indicated)	
4	Qty. required	12 Nos.	
5	Country of Origin	To be indicated	
6	Tread pattern	Lug Type (Industrial Type)	
7	Type	Tube Type Bias or Radial Ply	
8	Standards	Shall have ISO 9000 series standard certification for manufacturing process.	
9	Life Span	Guaranteed life span should be not less than 12 months from date of supply to SLPA. A Separate letter of Guaranty should be supplied with the offer.	
10	Thread Depth	Thread depth to be not less than 20 mm	
11	Max. Tyre load	Not less than 4000 kg at 8 bar 25 kmh speed.	
12	Punctures	i) Tyres to be puncture resistant ii) Side walls of the tyres to be reinforced in addition to casing ply (Heavy duty Nylon Ply construction can be accepted)	
13	Tyre Pressure	Tyre should be able to withstand an internal pressure of not less than 8 Bar	
14	Delivery Period	Delivery period shall be not more than 15 days.	

NOTE:

Copy of the catalogue should be supplied with **highlighting the recommended inflating pressure, thread depth & max tyre load**. The offers without the letter of guarantee and above information will be rejected. Delivery period is highly considered.