

Specifications for Lithium Base High Temp. Grease (EP 2 StarPlex)

| S/N | Description | SLPA's Requirement | Bidder's Compliance |
|-----|--------------------------|---|---------------------|
| 01 | General | EP2 StarPlex Grease , water resistant grease for automotive & industrial applications. | |
| 02 | Application | Shall be suitable for automotive wheel bearing, chassis lubrication & general industrial greasing. | |
| 03 | Product Specification | <ul style="list-style-type: none"> ➤ NLGI Grade 2 ➤ Worked penetration @ 25⁰C 256-285 ➤ Oil viscosity, mm²/s@ 40⁰C :- ≤ 220 mm²/s@ 100⁰C :- ≥ 21 ➤ Dropping point: ≥ 230⁰C | |
| 04 | Features / Benefits | 01) To be excellent water resistance. 02) To be rust & corrosion protection. 03) To be excellent oxidation resistance. 04) To be the anti-wear protection. 05) To be resists softening due to heat. | |
| 05 | Make / Country of origin | To be indicated | |
| 06 | Performance Standards | ISO 9000 series standards certification for manufacturing process (Copies of certificates to be attached) | |
| 07 | Delivery Period | Delivery period shall be clearly mentioned & not more than 02 weeks. | |
| 08 | Quantity Required | 150 Kg. | |

Authorized Signature: - ...

Company seal: -...

Company Name: -...

Note:-

1. Bidder should duly fill the "Bidder's compliance" column in the schedule of technical specifications. All blanks should be filled with words or figures, without just ticking. The bids which do not comply with the instructions are liable to rejection, without further enquiry.
2. The original catalogues/ manuals/Certificates (or clear & legible photocopies) in support of information required by Technical Specifications shall be submitted along with the bids, failing of which may lead to rejection of offer.