

**SPECIFICATIONS FOR INDUSTRIAL TIRES 700x15 6 PLY (Tube Less)**

	<b>Description</b>	<b>SLPA's Requirement</b>	<b>Supplier's Specifications</b>
1	General	To be Heavy duty Industrial Tubeless <b>Skid Steer tyre</b> and classified by manufacturer for the use of Skid Steer Loaders & Dozers. (JCB 1CX New )	
2	Size	700x15 6 PR	
3	Make	To be of reputed make (Make to be indicated)	
4	Qty. required	10 Nos.	
5	Country of Origin	To be indicated	
6	Lug Type	Industrial Type	
7	Ply & Type	i) 6 Ply Rating ii) Tubeless	
8	Standards	Should have ISO 9000 series standards certification for manufacturing process	
9	Life Span	Guaranteed life span should be not less than 1500 hours or 06 months for running on rough surface.	
10	Resistant to oils	To be oil resistant	
11	Thread Depth	Thread depth to be not less than 15 mm	
12	Max. Tyre load	Not less than 1400 kg at 4 bar pressure & 08 kmh. speed.	
13	Punctures	i) Tyres to be puncture resistant ii) Side walls of the tyres to be heavy duty	
14	Thread	To be specially designed to suit for rough handling on Abrasive surface.	
15	Tyre Pressure	Tyre should be able to withstand an internal pressure of not less than 58 PSI at inflating.	
16	Delivery Period	From Ex stocks	

**NOTE:**

Copies of the catalogue should be supplied with **highlighting the recommended Application, inflating pressure, thread depth & max tyre load.** The offers without the letter of guarantee and above information will be rejected.