

**SPECIFICATIONS FOR MOTOR TYRES TUBELESS 12.5/80x18 - 12PR**

	<b>Description</b>	<b>SLPA's Requirement</b>	<b>Supplier's Specifications</b>
1	General	To be Heavy duty Industrial Tubeless Tyre and classified by manufacturer for the use of Backhoe Loaders & Dozers (JCB 3DX- Front/ 2CX-All Tyres)	
2	Size	12.5/80 X 18 - 12 PR	
3	Make	To be of reputed make (Make to be indicated)	
4	Qty. required	05 Nos.	
5	Country of Origin	To be indicated	
6	Lug Type	Industrial Type-Lug	
7	Ply & Type	i) 12 Ply Rating ii) Tubeless	
8	Standards	Should have ISO 9000 series standards certification for manufacturing process.	
9	Life Span	Guaranteed life span should be not less than 1500 hours or 12 months for running on rough surface.	
10	Thread Depth	Thread depth to be not less than 25 mm	
11	Max. Tyre load	Not less than 2000 kg at 40 km/hr. speed	
12	Punctures	i) Tyres to be puncture resistant ii) Side walls of the tyres to be reinforced in addition to casing ply	
13	Thread	To be specially designed to suit for rough handling on Abrasive surface.	
14	Tyre Pressure	Tyre should be able to withstand an internal pressure of not less than 50 PSI at inflating.	
15	Delivery Period	30 days	

**NOTE:**

Copies of the catalogues and certificates should be supplied with **highlighting the recommended Application, inflating pressure, thread depth & max tyre load**. The offers without the letter of guarantee and above information will be rejected.