

Specifications for the Web Slings**Notes to the bidders**

- All the specifications of the offered item shall be clearly filled under the column, caption as "Specifications of the Offer". The offers submitted with a blank schedule of specification sheet or filled with "√" marks against the specifications will not be considered in the evaluation.
- Low quality, non-branded items are not considered in the evaluation.
- Proven original literatures, proof testing certificates shall be submitted to each item at the delivery and copies for the evaluation.

SLPA Specifications		Specifications of the Offer
General		
Heavy duty, high quality, non-abrasive web slings shall be of reputed make, sale and service by a reputed agent in Sri Lanka.		
Make	To be mentioned.	
Model	To be mentioned.	
Country of origin	To be mentioned.	
Country of manufacturing	To be mentioned.	
Warranty	The web sling shall be guaranteed for a minimum period of 06 months against the production / design faults and inferior quality. The warranty certificate shall be submitted at the delivery.	
Literature	Following literatures in English shall be provided with the offer;	
	1. Product brochure from the original catalogue	
	2. Colour picture of an offered item	
	3. Load test certificate	
Sample	Either by submission of sample or arrangement to inspect sample at the convenient location shall be arranged by the bidder.	
Standard		
Slings shall be conformed to the BS 3481 LT2 1983 or equivalent standard		

SLPA Specifications		Specifications of the Offer
Specifications		
<p>TAPERED FABRIC EYE Slings can be made with different size fabric eyes to fit any size hardware or any type lift.</p> <p>SLIDING CHINE Prevents rubbing on hull and protects sling from sharp corners.</p> <p>PROTECTIVE FLAP Protects hull of boat from disconnect pin hardware.</p> <p>EDGE GUARD Helps protect edges and prolong sling life.</p> <p>EXTRA EYE Permits lifting of different size boats with one set of slings. Available for most sling styles.</p>		
Usage	Shall be able to handle boats, large packages	
Material	Polyester	
Type	Twisted eye	
Load	25 Ton (Basket hitch)	
Length	Not less than 40 ft.	
Construction	Shall be double plies or higher plies so that maintaining flexible adaptation to hull configuration to cradle load	
Safety factor	6:1	
Fittings and Accessories		
Fully wrapped wear pads shall be provided for total eye protection for rough attachment points (eye reinforcement).		
Edge guard wear pads shall be provided for the edge protection for the prolonged use.		
Sliding chine & knee pads shall be included to permit positioning padding at any point to prevent rubbing on hull and to protect sling from sharp corners.		
Lead weights shall be sewn into the keel pad for fixing or sliding, and promotes rapid sinking of the sling.		
Extra sewn eyes shall be included to permit lifting of different sizes of boats with one set of slings.		
Disconnect permits removal of sling from beneath the boat without removing sling eye from hook. Protective flap shall be included.		